


Hydraulic Wrench SC type

**Never
jams!
No need
for a
disengage
button!**





Powerful!



Thanks to its outstanding speed, ergonomics and safety, this hydraulic square drive tool sets standards in almost every bolting situation.



The optional Safety-Hold grip with quick adjustment and lock provides maximum safety with unequalled flexibility.




Optionally with swivelling hose connection (lower speed due to reduced flow volume)



360° rotation angle

Perfected!

The MX-EC/MSX is preferred by users for its reliable and practical design. You will not find a disengage lever or button - none is needed. **Our hydraulic bolting tools do not jam.**



**Continuous rotation in every stroke position!
No jamming!**

**Also available as
single hose model**



- **Long-life Plarad quality**
- **High bolting speeds thanks to optimum harmonization with Plarad power packs**
- **Torque range 200 – 65,000 Nm**
- **Operating pressure up to 800 bar (11,600 psi)**
- **Automatically opening and closing pressure safety valve**
- **SQS high-pressure safety cylinder**
 - **very service friendly**
 - **high safety**
- **Very small dimensions thanks to spherical drive system**
- **Fine spline ratchet system**
 - **high torque precision**
 - **no jamming**
- **Also available as ATEX version (II 2 G c II B T4) for Zone 1G**
- **Internationally patented technology**

Adjustable!



The reaction arm can be quickly and easily rotated by 360°. The safety latch reliably prevents inadvertent un-locking.



Type

Square-drive

Torque-range (Nm)

PL 210SC

25.4 mm

210 - 2,100

PL 450SC

25.4 mm

450 - 4,500

PL 750SC

38.1 mm

750 - 7,500

PL 950SC

38.1 mm

950 - 9,500

PL 1200SC

38.1 mm

1,200 - 12,000

PL 1500SC

38.1 mm

1,550 - 15,500

PL 2000SC

63.5 mm

2,000 - 20,000

PL 2500SC

63.5 mm

2,500 - 25,000

PL 4000SC

63.5 mm

4,000 - 40,000

PL 6500SC

88.9 mm

6,500 - 65,000

PLARAD

A comprehensive range of accessories allows a large number of different applications.

Standard square drive sockets are available in all dimensions and wrench sizes.



Double hexagonal socket


Long socket

Direct drive sockets reduce height and weight



Direct drive hex inserts in a variety of sizes





PLARAD[®]
Torque & Tension Systems



255-6 Furusato Iwaoka-cho Nishiku Kobe city 651-2404 Japan

<http://www.plarad.net/>

E-Mail : info@plarad.net

Phone : +81-78-967-3556

FAX : +81-78-967-3567